

WHEELS

Product group	Wheels
Item number	59967798
Valid wheel size	385 / 55 R 22.5
Brand	Windpower
Tread pattern	WTR 69
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	M20/M22
Offset (mm)	+120
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466617
LI / SI / PR	158 L (160 J), 20 PR
Load capacity 1 [kg]	4250
Speed 1 [km/h].	120
Load capacity 2 [kg]	4500
Speed 2 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	117,30
ECE regulation number	ECE 54 ECE 117
Section width (mm)	381
Stat. radius (SLR) [mm]	499
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3074
Tread depth (mm)	16,5
Rolling resistance	C
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30963041
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB

Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No