

WHEELS

Product group	Wheels
Item number	59967802
Valid wheel size	245 / 70 R 19.5
Brand	Windpower
Tread pattern	WTL 32
Valid rim size	7.50 x 19.5
Rim connection	8/221/275
Bolt hole design	A33
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	100



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466454
LI / SI / PR	141 / 140 J, 18 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	100
Load capacity 3 [kg]	2500
Speed 3 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	69,73
ECE regulation number	ECE 54 ECE 117
Section width (mm)	253
Stat. radius (SLR) [mm]	433.00
Rolling circumference [mm].	2559
Tread depth (mm)	13,5
Rolling resistance	D
Wet grip	B
Rolling noise [db].	71
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 31267876
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3150
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC

Number of bolt holes	8
Bolt hole design EUWA	M22 ES 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade