

WHEELS

Product group	Wheels
Item number	59967812
Valid wheel size	445 / 45 R 19.5
Brand	Linglong
Tread pattern	A-D90
Valid rim size	14.00 x 19.5
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 11366516
LI / SI / PR	164 D, 24 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	65
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,49
ECE regulation number	ECE 106
Section width (mm)	446

Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2712
Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 31267911
Load capacity of rim 1 [kg]	4600
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	65
Maximum air pressure [bar].	9,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade