

WHEELS

Product group	Wheels
Item number	59967816
Valid wheel size	445 / 45 R 19.5
Brand	Linglong
Tread pattern	T820
Valid rim size	14.00 x 19.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 11366115
LI / SI / PR	160 J, 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	100
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	110,24
ECE regulation number	ECE 54 ECE 117

Section width (mm)	446
Stat. radius (SLR) [mm]	422.00
Rolling circumference [mm].	2711
Tread depth (mm)	15,5
Rolling resistance	C
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 31267917
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No