

WHEELS

Product group	Wheels
Item number	59967862
Valid wheel size	385 / 65 R 22.5
Brand	Continental
Tread pattern	Conti Hybrid HT3+
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Offset (mm)	+34
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	110



Technical Informations

Assembly Item no. Tyres	• 10000884
LI / SI / PR	164 K
Load capacity 1 [kg]	5000
Speed 1 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	123,53
ECE regulation number	ECE 117 ECE 54

Section width (mm)	381
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3261
Tread depth (mm)	16,0
Rolling resistance	B
Wet grip	B
Rolling noise [db].	70
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 33060254
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	14
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade