

## WHEELS

Product group	Wheels
Item number	59967885
Valid wheel size	385 / 65 R 22.5
Brand	Windpower
Tread pattern	WTR 69
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	M20/M22
Offset (mm)	+120
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100



**WINDPOWER**  
Get Your Job Done

## Technical Informations

Assembly Item no. Tyres	• 10466745
LI / SI / PR	160 K (158 L), 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	119,80
ECE regulation number	ECE 54 ECE 117
Section width (mm)	384
Stat. radius (SLR) [mm]	499
Rolling circumference [mm].	3260
Tread depth (mm)	16,8
Rolling resistance	C
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30963041
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10

---

<b>Bolt hole design EUWA</b>	M22
<b>Bolt hole diameter [mm]</b>	26
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	9.7
<b>Preassembled valve</b>	No