

WHEELS

Product group	Wheels
Item number	59967886
Valid wheel size	385 / 65 R 22.5
Brand	Windpower
Tread pattern	WTR 69+
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	100



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466744
LI / SI / PR	164 K (158 L), 20 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	119,80
ECE regulation number	ECE 54 ECE 117
Section width (mm)	384
Stat. radius (SLR) [mm]	499
Rolling circumference [mm].	3260
Tread depth (mm)	16,8
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 30963034
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36

Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No