

WHEELS

Product group	Wheels
Item number	59967893
Valid wheel size	385 / 65 R 22.5
Brand	Sailun
Tread pattern	STL1
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 11066384
LI / SI / PR	164 K (158 L), 20 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	120,11
ECE regulation number	ECE 54 ECE 117
Section width (mm)	389
Stat. radius (SLR) [mm]	495.96
Rolling circumference [mm].	3103
Tread depth (mm)	13,0
Rolling resistance	B
Wet grip	B
Rolling noise [db].	71
Rolling noise level	A
E-Ready	No
Assembly Item no. Rim	• 10001097
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13.5
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	10

Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No