

WHEELS

Product group	Wheels
Item number	59967914
Valid wheel size	425 / 65 R 22.5
Brand	Windpower
Tread pattern	WGC 28
Valid rim size	14.00 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	100



WINDPOWER
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466681
LI / SI / PR	165 K, 20 PR
Load capacity 1 [kg]	5150
Speed 1 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	140,93
ECE regulation number	ECE 54 ECE 117

Section width (mm)	421
Stat. radius (SLR) [mm]	519.00
Rolling circumference [mm].	3419
Tread depth (mm)	16,5
Rolling resistance	C
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 33060305
Load capacity of rim 1 [kg]	6100
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	8,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36

Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade