

WHEELS

Product group	Wheels
Item number	59967978
Valid wheel size	12.00 R 24
Brand	Windpower
Tread pattern	WGC 52
Valid rim size	8.5 - 24
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+180
Half centre distance (HMA) [mm]	195
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100





Technical Informations

Assembly Item no. Tyres •	10468192
LI / SI / PR	160 / 157 K, 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
Load capacity 3 [kg]	4125
Speed 3 [km/h].	110
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Tyre colour	Black
Nettogewicht [kg] (gültig)	160,60
ECE regulation number	ECE 54 ECE 117
Section width (mm)	314
Stat. radius (SLR) [mm]	567.00
Rolling circumference [mm].	3733
Tread depth (mm)	17,5
Rolling resistance	С
Wet grip	В
Rolling noise [db].	74
Rolling noise level	В
E-Ready	No
Assembly Item no. Rim •	30060045
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Number of bolt holes	10
Bolt hole design EUWA	M22
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	mehrteilig
Rim centering	НВ
Rim material	steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	Internal Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No