

WHEELS

Product group	Wheels
Item number	59967981
Valid wheel size	445 / 65 R 22.5
Brand	Alliance
Tread pattern	398
Valid rim size	13.00 X 22.5
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+120
Half centre distance (HMA) [mm]	132.8
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 15216272
LI / SI / PR	160 J
Load capacity 1 [kg]	4500
Speed 1 [km/h].	100
Carcass properties	All-Steel POR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	157,58
ECE regulation number	ECE 54
Section width (mm)	455

Stat. radius (SLR) [mm]	532
Rolling circumference [mm].	3592
Tread depth (mm)	30,0
E-Ready	No
Assembly Item no. Rim	• 31460213
Load capacity of rim 1 [kg]	5150
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	100
Maximum air pressure [bar].	6,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No