

WHEELS

Product group	Wheels
Item number	59970065
Valid wheel size	6.00 - 9 / 4.00 E
Brand	BKT
Tread pattern	Maglift
Valid rim size	4.00 E - 9
Rim connection	5/67.0/112
Bolt hole design	G12
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	1150
Speed complete wheel [km/h]	25



Technical Informations

Assembly Item no. Tyres	• 15770084
Carcass properties	STD Solid Rubber
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18.17
ECE regulation number	not necessary
Section width (mm)	141
Side panel width [mm]	141
Tread width (mm)	125
Overall width [mm].	145
Tread depth (mm)	19,0

E-Ready	No
Assembly Item no. Rim	• 30691315
Load capacity of rim 1 [kg]	1150
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	710
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	25
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	geteilt
Quantity multi-piece	two-part
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Rim design industry	Standard
Disc thickness [mm]	12
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	67.0
Bolt hole circle diameter [mm]	112
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
