

WHEELS

Product group	Wheels
Item number	59991105
Valid wheel size	300 / 65 - 12
Brand	BKT
Tread pattern	Rib 775
Valid rim size	8.50 I x 12 H2
Rim connection	5/110/160
Bolt hole design	A1
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711310
LI / SI / PR	116 A8, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	32,48
ECE regulation number	ECE 106
Section width (mm)	305
Stat. radius (SLR) [mm]	304

Rolling circumference [mm].	2007
Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 31610048
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	1350
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,60
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
hub hole diameter [mm].	110
Bolt hole circle diameter [mm]	160
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Hump	H2
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No

TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade