

WHEELS

Product group	Wheels
Item number	59991251
Valid wheel size	26 x 12 - 12
Brand	BKT
Tread pattern	Skid Power HD
Valid rim size	10.50 I x 12 H2
Rim connection	5/66.6/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	1000
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	15772054
LI / SI / PR	114 A8, 12 PR
Load capacity 1 [kg]	1180
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	31,65
ECE regulation number	ECE 106
Section width (mm)	305
Stat. radius (SLR) [mm]	297
Rolling circumference [mm].	1947

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Tread depth (mm)	23,5
E-Ready	No
Assembly Item no. Rim •	31610062
Load capacity of rim 1 [kg]	1100
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,40
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Valve design	Metal valve
Valve length [mm]	42.0
Valve angle [°]	gerade