

WHEELS

Product group	Wheels
Item number	59991252
Valid wheel size	27 x 10 - 12
Brand	BKT
Tread pattern	Power Trax HD Forklift
Valid rim size	8.00 G - 12
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3150
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15771107
LI / SI / PR	148 A8, 20 PR
Load capacity 1 [kg]	3150
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	44,61
ECE regulation number	ECE 106
Section width (mm)	255
Tread depth (mm)	22,0
E-Ready	No

Assembly Item no. Rim	• 31610043
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	10,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	four-part
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Rim design industry	Standard
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No