

WHEELS

Product group	Wheels
Item number	59991299
Valid wheel size	27 x 8.50 - 15
Brand	BKT
Tread pattern	Skid Power HD
Valid rim size	7 J x 15
Rim connection	5/66.5/112
Bolt hole design	B1
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	850
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15772061
LI / SI / PR	102 A8, 8 PR
Load capacity 1 [kg]	850
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	30,69
ECE regulation number	ECE 106
Section width (mm)	218
Stat. radius (SLR) [mm]	324
Rolling circumference [mm].	2004

Tread depth (mm)	14,5
E-Ready	No
Assembly Item no. Rim	• 31610140
Load capacity of rim 1 [kg]	1100
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	900
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,20
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 DS 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade