

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 59991352 |
| Valid wheel size | 27 x 10.5 - 15 |
| Brand | BKT |
| Tread pattern | Skid Power HD |
| Valid rim size | 8 W x 15 |
| Rim connection | 5/94/140 |
| Bolt hole design | A1 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 900 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|----------------------------|--------------|
| Assembly Item no. Tyres | • 15772091 |
| LI / SI / PR | 105 A8, 8 PR |
| Load capacity 1 [kg] | 925 |
| Speed 1 [km/h]. | 40 |
| Direction | Left |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 35,10 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 256 |
| Stat. radius (SLR) [mm] | 326 |

| | |
|-----------------------------|-------------------------------|
| Speed Radius Index (SRI) | 550 |
| Rolling circumference [mm]. | 2037 |
| Tread depth (mm) | 14,5 |
| E-Ready | No |
| Assembly Item no. Rim | • 31610083 |
| Load capacity of rim 1 [kg] | 1025 |
| Speed Rims 1 [km/h] | 25 |
| Load capacity of rim 2 [kg] | 900 |
| Speed Rims 2 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 4,20 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole design EUWA | B14 ES 28 |
| Bolt hole diameter [mm] | 18.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| hub hole diameter [mm]. | 94 |

| | |
|---------------------------------------|----------------|
| Bolt hole circle diameter [mm] | 140 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.3 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |