

WHEELS

Product group	Wheels
Item number	59991424
Valid wheel size	31 x 13.50 - 15
Brand	Maxxis
Tread pattern	C769
Valid rim size	10 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1200
Speed complete wheel [km/h]	30
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10711667
LI / SI / PR	8 PR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	44,01
ECE regulation number	not necessary
Section width (mm)	323
Rolling circumference [mm].	2442
E-Ready	No
Assembly Item no. Rim	• 32010093

Load capacity of rim 1 [kg]	1200
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	1100
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,10
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve

Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade