

WHEELS

Product group	Wheels
Item number	59991433
Valid wheel size	31 x 15.50 - 15
Brand	BKT
Tread pattern	Trac Master
Valid rim size	13 LB x 15 H2
Rim connection	5/66.5/112
Bolt hole design	A1
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15710560
LI / SI / PR	116 B, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	47,63
ECE regulation number	ECE 106
Section width (mm)	405
Stat. radius (SLR) [mm]	357
Rolling circumference [mm].	2365

Tread depth (mm)	18,0
E-Ready	No
Assembly Item no. Rim	• 30810137
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,10
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve

Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade