

WHEELS

Product group	Wheels
Item number	59991466
Valid wheel size	31 x 15.50 - 15
Brand	BKT
Tread pattern	TR 315
Valid rim size	13 LB x 15 H2
Rim connection	5/66.6/112
Bolt hole design	A1
Offset (mm)	-37
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	25
Nettogewicht [kg] (gültig)	47,69
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15710550
LI / SI / PR	116 B, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	50
Maximum air pressure [bar].	3,10
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	390
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2320
Tread depth (mm)	20,0
Number of lugs	18x2
Assembly Item no. Rim	• 32010104
Load capacity of rim 1 [kg]	1250
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	900
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	25
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	5
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Bolt hole design EUWA	B14 ES 28
Countersinking	Sphere
Spherical countersink [mm].	R14
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig

Hump	H2
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade