

## WHEELS

|                                   |                 |
|-----------------------------------|-----------------|
| Product group                     | Wheels          |
| Item number                       | 59991474        |
| Valid wheel size                  | 31 x 15.50 - 15 |
| Brand                             | BKT             |
| Tread pattern                     | TR 313          |
| Valid rim size                    | 13 LB x 15 H2   |
| Rim connection                    | 6/161/205       |
| Bolt hole design                  | E2              |
| Offset (mm)                       | -85             |
| Rim colour                        | Silver          |
| Load capacity complete wheel [kg] | 1250            |
| Speed complete wheel [km/h]       | 40              |



## Technical Informations

|                             |             |
|-----------------------------|-------------|
| Assembly Item no. Tyres     | • 15710552  |
| LI / SI / PR                | 116 B, 8 PR |
| Load capacity 1 [kg]        | 1250        |
| Speed 1 [km/h].             | 50          |
| Antistatic                  | No          |
| Tyre colour                 | Black       |
| Nettogewicht [kg] (gültig)  | 42,81       |
| ECE regulation number       | ECE 106     |
| Section width (mm)          | 370         |
| Stat. radius (SLR) [mm]     | 342         |
| Rolling circumference [mm]. | 2233        |

|                                |                               |
|--------------------------------|-------------------------------|
| Tread depth (mm)               | 23,5                          |
| Number of lugs                 | 19x2                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 30810140                    |
| Load capacity of rim 1 [kg]    | 1400                          |
| Speed Rims 1 [km/h]            | 40                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 3,10                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | H2                            |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 6                             |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| hub hole diameter [mm].        | 161                           |
| Bolt hole circle diameter [mm] | 205                           |
| Valve seat                     | External Valve                |
| Valve hole diameter [mm]       | 15.7                          |
| Preassembled valve             | No                            |
| Valve design                   | Rubber valve                  |

---

|                   |        |
|-------------------|--------|
| Valve length [mm] | 55.0   |
| Valve angle [°]   | gerade |

---