

## **WHEELS**

Product group	Wheels
Item number	59991486
Valid wheel size	31 x 15.50 - 15
Brand	Alliance
Tread pattern	Grassland Flotation 221
Valid rim size	13 LB x 15 H2
Rim connection	8/86.2/120
Offset (mm)	+98
Rim colour	Silver
Load capacity complete wheel [kg]	1380
Speed complete wheel [km/h]	40





## **Technical Informations**

Assembly Item no. Tyres	15211647
LI / SI / PR	118 A8 / 116 B, 8 PR
Load capacity 1 [kg]	1320
Speed 1 [km/h].	40
Load capacity 2 [kg]	1250
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	43,62
ECE regulation number	ECE 106
Section width (mm)	391

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Stat. radius (SLR) [mm]	353
Rolling circumference [mm].	2319
Tread depth (mm)	16,0
Tyre capacity 75% [ltr.]	118.7
E-Ready	No
Assembly Item no. Rim	32010102
Load capacity of rim 1 [kg]	1380
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,10
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	НВ
Number of bolt holes	8
Bolt hole diameter [mm]	13
hub hole diameter [mm].	86.2
Bolt hole circle diameter [mm]	120
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade