

## WHEELS

Product group	Wheels
Item number	59991494
Valid wheel size	31 x 15.50 - 15
Brand	Alliance
Tread pattern	Grassland Flotation 221
Valid rim size	13 LB x 15 H2
Rim connection	5/172/206.3
Offset (mm)	-6
Rim colour	Silver
Load capacity complete wheel [kg]	1800



## Technical Informations

Assembly Item no. Tyres	• 15211647
LI / SI / PR	118 A8 / 116 B, 8 PR
Load capacity 1 [kg]	1320
Speed 1 [km/h].	40
Load capacity 2 [kg]	1250
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	45,72
ECE regulation number	ECE 106
Section width (mm)	391

Stat. radius (SLR) [mm]	353
Rolling circumference [mm].	2319
Tread depth (mm)	16,0
Tyre capacity 75% [ltr.]	118.7
E-Ready	No
Assembly Item no. Rim	• 32010097
Load capacity of rim 1 [kg]	1800
Speed Rims 1 [km/h]	15
Maximum speed [km/h].	15
Maximum air pressure [bar].	3,10
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	5
Bolt hole diameter [mm]	17.1
hub hole diameter [mm].	172
Bolt hole circle diameter [mm]	206.3
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

---

Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade