

WHEELS

| | |
|-----------------------------------|-------------------------|
| Product group | Wheels |
| Item number | 59991512 |
| Valid wheel size | 33 x 15.50 - 15 |
| Brand | Alliance |
| Tread pattern | Grassland Flotation 221 |
| Valid rim size | 13 LB x 15 H2 |
| Rim connection | 5/192/225 |
| Bolt hole design | A1 |
| Offset (mm) | +83.5 |
| Rim colour | Grey |
| Load capacity complete wheel [kg] | 1550 |
| Speed complete wheel [km/h] | 50 |



Technical Informations

| | |
|-----------------------------|-------------|
| Assembly Item no. Tyres | • 15211646 |
| LI / SI / PR | 123 B, 8 PR |
| Load capacity 1 [kg] | 1550 |
| Speed 1 [km/h]. | 50 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 53,47 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 390 |
| Stat. radius (SLR) [mm] | 375 |
| Rolling circumference [mm]. | 2530 |

| | |
|--------------------------------|-------------------------------|
| Tread depth (mm) | 15,0 |
| E-Ready | No |
| Assembly Item no. Rim | • 39600371 |
| Load capacity of rim 1 [kg] | 1900 |
| Speed Rims 1 [km/h] | 25 |
| Load capacity of rim 2 [kg] | 1730 |
| Speed Rims 2 [km/h] | 40 |
| Maximum speed [km/h]. | 50 |
| Maximum air pressure [bar]. | 3,10 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL7042 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 5 |
| Bolt hole design EUWA | B14 ES 28 |
| Bolt hole diameter [mm] | 18.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| hub hole diameter [mm]. | 192 |
| Bolt hole circle diameter [mm] | 225 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |

| | |
|-------------------------|-------------|
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |