

## WHEELS

Product group	Wheels
Item number	59991517
Valid wheel size	31 X 15.50 R 15
Brand	BKT
Tread pattern	AS 511
Valid rim size	13 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-55
Rim colour	Silver
Load capacity complete wheel [kg]	1500
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15717160
LI / SI / PR	122 B
Load capacity 1 [kg]	1500
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	47,77
ECE regulation number	ECE 106
Section width (mm)	388
Stat. radius (SLR) [mm]	353
Speed Radius Index (SRI)	380

Rolling circumference [mm].	2387
Tread depth (mm)	18,5
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 32010103
Load capacity of rim 1 [kg]	2000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No
Valve design	Rubber valve

---

Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade