

WHEELS

Product group	Wheels
Item number	59991518
Valid wheel size	31 X 13.50 - 15
Brand	BKT
Tread pattern	Flotation Rib Implement
Valid rim size	10 LB x 15 H2
Rim connection	6/161/205
Offset (mm)	-12.5
Load capacity complete wheel [kg]	1550
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711694
LI / SI / PR	124 B, 12 PR
Load capacity 1 [kg]	1600
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	49,44
ECE regulation number	ECE 106
Section width (mm)	360
Stat. radius (SLR) [mm]	359
Rolling circumference [mm].	2129

Tread depth (mm)	9,0
E-Ready	No
Assembly Item no. Rim	• 32010092
Load capacity of rim 1 [kg]	1550
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,20
Hump	H2
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	John Deere - yellow
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade