

WHEELS

Product group	Wheels
Item number	59991523
Valid wheel size	31 x 15.5 - 15
Brand	BKT
Tread pattern	Skid Power HD
Valid rim size	13 x 15
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+70
Rim colour	Silver
Load capacity complete wheel [kg]	1650
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15772094
LI / SI / PR	125 A8, 10 PR
Load capacity 1 [kg]	1650
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	56,69
ECE regulation number	ECE 106
Section width (mm)	400
Stat. radius (SLR) [mm]	378
Speed Radius Index (SRI)	550

Rolling circumference [mm].	2411
Tread depth (mm)	21,0
E-Ready	No
Assembly Item no. Rim	• 33060016
Load capacity of rim 1 [kg]	3300
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,20
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade