Bohnenkamp Moving Professionals

WHEELS

Product group	Wheels
Item number	59991531
Valid wheel size	33 x 15.5 - 16.5
Brand	ВКТ
Tread pattern	Skid Power HD
Valid rim size	12.00 x 16.5
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+35
Rim colour	Silver
Load capacity complete wheel [kg]	3150
Speed complete wheel [km/h]	10
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	15772155
LI / SI / PR	148 A2, 12 PR
Load capacity 1 [kg]	3150
Speed 1 [km/h].	10
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	68,22
ECE regulation number	ECE 106
Section width (mm)	394

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

17.11.2024

Stat. radius (SLR) [mm]	387
Rolling circumference [mm].	2563
Tread depth (mm)	21,5
E-Ready	No
Assembly Item no. Rim	33060115
Load capacity of rim 1 [kg]	4450
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3750
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	10
Maximum air pressure [bar].	4,10
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.