

WHEELS

Product group	Wheels
Item number	59994497
Valid wheel size	460 / 85 R 38
Brand	Alliance
Tread pattern	Agri Star II
Valid rim size	DW 16 L X 38
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-125
Rim colour	Silver
Load capacity complete wheel [kg]	5450
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15228745
LI / SI / PR	167 D
Load capacity 1 [kg]	5450
Speed 1 [km/h].	65
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	312,75
ECE regulation number	ECE 106
Section width (mm)	480
Stat. radius (SLR) [mm]	819

Speed Radius Index (SRI)	875
Rolling circumference [mm].	5394
Tread depth (mm)	53,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	408.68
E-Ready	No
Assembly Item no. Rim	• 39123178
Load capacity of rim 1 [kg]	5450
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,40
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade