

## WHEELS

Product group	Wheels
Item number	59994623
Valid wheel size	IF 520 / 85 R 42
Brand	Alliance
Tread pattern	Agriflex 372
Valid rim size	DW 18 L x 42
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	5800
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15227395
LI / SI / PR	169 D
Load capacity 1 [kg]	5800
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	394,65
ECE regulation number	ECE 106
Section width (mm)	538
Stat. radius (SLR) [mm]	870

Speed Radius Index (SRI)	925
Rolling circumference [mm].	5772
Tread depth (mm)	55,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	569
E-Ready	No
Assembly Item no. Rim	• 39123053
Load capacity of rim 1 [kg]	7060
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

---

<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade