

WHEELS

Product group	Wheels
Item number	59994647
Valid wheel size	VF 520 / 85 R 46
Brand	Alliance
Tread pattern	Agriflex 354 +
Valid rim size	DW 18 L x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-75
Rim colour	Silver
Load capacity complete wheel [kg]	6000
Speed complete wheel [km/h]	65



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Technical Informations

Assembly Item no. Tyres	• 15226328
LI / SI / PR	170 D
Load capacity 1 [kg]	6000
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	429,65
ECE regulation number	ECE 106
Section width (mm)	535
Stat. radius (SLR) [mm]	906

Speed Radius Index (SRI)	975
Rolling circumference [mm].	6050
Tread depth (mm)	53,0
Number of lugs	29x2
Tyre capacity 75% [ltr.]	606
E-Ready	No
Assembly Item no. Rim	• 39123142
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	1,60
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade