

## WHEELS

|                                   |                |
|-----------------------------------|----------------|
| Product group                     | Wheels         |
| Item number                       | 59994652       |
| Valid wheel size                  | 340 / 85 R 48  |
| Brand                             | BKT            |
| Tread pattern                     | Agrimax RT 955 |
| Valid rim size                    | W 12 x 48      |
| Rim connection                    | 10/281/335     |
| Bolt hole design                  | B3             |
| Offset (mm)                       | +100           |
| Rim colour                        | Silver         |
| Load capacity complete wheel [kg] | 3550           |
| Speed complete wheel [km/h]       | 40             |



## Technical Informations

|                            |                |
|----------------------------|----------------|
| Assembly Item no. Tyres    | • 15727610     |
| LI / SI / PR               | 152 A8 / 152 B |
| Load capacity 1 [kg]       | 3550           |
| Speed 1 [km/h].            | 40             |
| Load capacity 2 [kg]       | 3550           |
| Speed 2 [km/h].            | 50             |
| Antistatic                 | No             |
| Tyre colour                | Black          |
| Nettogewicht [kg] (gültig) | 284,36         |
| ECE regulation number      | ECE 106        |
| Section width (mm)         | 353            |

|                                |                               |
|--------------------------------|-------------------------------|
| Stat. radius (SLR) [mm]        | 855                           |
| Rolling circumference [mm].    | 5572                          |
| Tread depth (mm)               | 36,5                          |
| Number of lugs                 | 29x2                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 39123013                    |
| Load capacity of rim 1 [kg]    | 4620                          |
| Speed Rims 1 [km/h]            | 65                            |
| Maximum speed [km/h].          | 50                            |
| Maximum air pressure [bar].    | 4,00                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | kein Hump                     |
| Valve protection               | VS H                          |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 10                            |
| Bolt hole design EUWA          | B22 DS 36                     |
| Bolt hole diameter [mm]        | 27                            |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |

---

|                          |                |
|--------------------------|----------------|
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| Valve design             | Metal valve    |
| Valve designation ETRTO  | V5.01.1        |
| Valve length [mm]        | 50.0           |
| Valve angle [°]          | gerade         |