

WHEELS

Product group	Wheels
Item number	59994653
Valid wheel size	380 / 90 R 46
Brand	Alliance
Tread pattern	350
Valid rim size	W 13 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	6900
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15226322
LI / SI / PR	175 A8 / 172 D
Load capacity 1 [kg]	6900
Speed 1 [km/h].	40
Load capacity 2 [kg]	6300
Speed 2 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	358,66
ECE regulation number	ECE 106

Section width (mm)	378
Stat. radius (SLR) [mm]	864
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5633
Tread depth (mm)	40,5
Tyre capacity 75% [ltr.]	315
E-Ready	No
Assembly Item no. Rim	• 39123052
Load capacity of rim 1 [kg]	6869
Speed Rims 1 [km/h]	50
Maximum speed [km/h].	65
Maximum air pressure [bar].	5,80
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade