

## WHEELS

Product group	Wheels
Item number	59994656
Valid wheel size	VF 380 / 90 R 46
Brand	Alliance
Tread pattern	Agriflex 354 +
Valid rim size	W 13 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+85
Rim colour	Silver
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	65



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Technical Informations

Assembly Item no. Tyres	• 15226327
LI / SI / PR	173 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	329,01
ECE regulation number	ECE 106
Section width (mm)	391
Stat. radius (SLR) [mm]	854

Rolling circumference [mm].	5633
Tread depth (mm)	48,5
Number of lugs	32x2
Tyre capacity 75% [ltr.]	398
E-Ready	No
Assembly Item no. Rim	• 39123058
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,40
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Colour type	Glossy
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade