

WHEELS

Product group	Wheels
Item number	59994667
Valid wheel size	IF 380 / 90 R 46
Brand	Alliance
Tread pattern	Agriflex 363
Valid rim size	W 13 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	5600
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15226890
LI / SI / PR	168 D
Load capacity 1 [kg]	5600
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	338,61
ECE regulation number	ECE 106
Section width (mm)	389
Stat. radius (SLR) [mm]	853

Rolling circumference [mm].	5592
Tread depth (mm)	39,0
Number of lugs	34x2
Tyre capacity 75% [ltr.]	315
E-Ready	No
Assembly Item no. Rim	• 39123115
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,40
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade