

## **WHEELS**

Product group	Wheels
Item number	59995059
Valid wheel size	13 x 5.00 - 6
Brand	ВКТ
Tread pattern	LG 306
LI / SI / PR	52 A3 / 48 A6, 4 PR
TL/TT	TL
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	90
Hub length [mm]	90
Rim colour	Silver
Load capacity complete wheel [kg]	200
Speed complete wheel [km/h]	15



## **Technical Informations**

Assembly Item no. Tyres	15710323
LI / SI / PR	52 A3 / 48 A6, 4 PR
TL/TT	TL
Brand	BKT
Tread pattern	LG 306
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	2,80
Section width (mm)	127
Stat. radius (SLR) [mm]	144
Rolling circumference [mm].	943
Tread depth (mm)	4,0
Assembly Item no. Rim •	30895080
Valid rim size	4.50 A x 6
Load capacity of rim 1 [kg]	360
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	300
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	15
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Verschweißung beidseitig	No
Offset hub	No No
Additional socket required	No No
Valve seat	External Valve