

WHEELS

Product group	Wheels
Item number	59995060
Valid wheel size	15 x 6.00 - 6
Brand	Deli
Tread pattern	S-317
LI / SI / PR	61 A6, 4 PR
т⊔тт	TT
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	90
Hub length [mm]	90
Rim colour	Silver
Load capacity complete wheel [kg]	257
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	19110090
LI / SI / PR	61 A6, 4 PR
TL/TT	тт
Brand	Deli
Tread pattern	S-317
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Maximum air pressure [bar].	
maximum air pressure [bar].	2,10
Section width (mm)	154
Stat. radius (SLR) [mm]	155
Rolling circumference [mm].	1020
Tread depth (mm)	3,5
Assembly Item no. Rim •	30895080
Valid rim size	4.50 A x 6
Load capacity of rim 1 [kg]	360
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	300
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	30
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve