

## WHEELS

Product group	Wheels
Item number	59995275
Valid wheel size	8.15 - 15
Brand	BKT
Tread pattern	PL 801
Valid rim size	6.5 - 15
Rim connection	10/176/225
Bolt hole design	B3
Offset (mm)	+124
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Load capacity complete wheel [kg]	2650
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15771130
LI / SI / PR	142 A8, 14 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	54.92
ECE regulation number	ECE 106
Section width (mm)	215
Tread depth (mm)	19,5

E-Ready	No
Assembly Item no. Rim	• 30060040
Load capacity of rim 1 [kg]	2650
Speed Rims 1 [km/h]	105
Maximum speed [km/h].	40
Maximum air pressure [bar].	10,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Preassembled valve	No