

WHEELS

Product group	Wheels
Item number	59995280
Valid wheel size	8.15 - 15
Brand	BKT
Tread pattern	PL 801
Valid rim size	6.5 - 15
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+124
Half centre distance (HMA) [mm]	134
Rim colour	Silver
Load capacity complete wheel [kg]	2300
Speed complete wheel [km/h]	25



Technical Informations

Assembly Item no. Tyres	• 15771130
LI / SI / PR	142 A8, 14 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	50,52
ECE regulation number	ECE 106
Section width (mm)	215
Tread depth (mm)	19,5

E-Ready	No
Assembly Item no. Rim	• 30060020
Load capacity of rim 1 [kg]	2300
Speed Rims 1 [km/h]	105
Maximum speed [km/h].	25
Maximum air pressure [bar].	10,00
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	mehrteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	Internal Valve
Preassembled valve	No