

WHEELS

Product group	Wheels
Item number	59995373
Valid wheel size	23.1 / 18 - 26
Brand	Alliance
Tread pattern	330
Valid rim size	DW 20 A x 26
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5600
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15222357
LI / SI / PR	168 A8, 16 PR
Load capacity 1 [kg]	5600
Speed 1 [km/h].	40
Carcass properties	HD
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	232,97
ECE regulation number	ECE 106
Section width (mm)	587
Stat. radius (SLR) [mm]	690

Rolling circumference [mm].	4545
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 32010404
Load capacity of rim 1 [kg]	6000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	5400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve

Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade