

WHEELS

Product group	Wheels
Item number	59995550
Valid wheel size	400 / 45 L - 17.5
Brand	Deli
Tread pattern	SG-815
Valid rim size	14.00 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4000
Speed complete wheel [km/h]	50
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19172460
LI / SI / PR	156 B
Load capacity 1 [kg]	4000
Speed 1 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	82,80
ECE regulation number	ECE 106
Section width (mm)	392
Stat. radius (SLR) [mm]	348

Rolling circumference [mm].	2285
Tread depth (mm)	13,5
E-Ready	No
Assembly Item no. Rim	• 33060110
Load capacity of rim 1 [kg]	6150
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	5200
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	6,00
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade