

WHEELS

Product group	Wheels
Item number	59996014
Valid wheel size	16 x 6.50 - 8
Brand	BKT
Tread pattern	TR 315
Valid rim size	5.50 A x 8
Rim connection	4/60/100
Bolt hole design	D12
Rim colour	Silver
Load capacity complete wheel [kg]	355
Speed complete wheel [km/h]	15



Technical Informations

Assembly Item no. Tyres	• 15710380
LI / SI / PR	72 A3 / 68 A6, 6 PR
Load capacity 1 [kg]	355
Speed 1 [km/h].	15
Load capacity 2 [kg]	315
Speed 2 [km/h].	30
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	6,11
ECE regulation number	ECE 106
Section width (mm)	155

Stat. radius (SLR) [mm]	182
Rolling circumference [mm].	1183
Tread depth (mm)	10,0
E-Ready	No
Assembly Item no. Rim	• 30655030
Load capacity of rim 1 [kg]	575
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	350
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	30
Maximum air pressure [bar].	2,90
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	16
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	100
Valve seat	External Valve

Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade