

WHEELS

Product group	Wheels
Item number	59996021
Valid wheel size	16 x 6.50 - 8
Brand	BKT
Tread pattern	TR 315
LI / SI / PR	72 A3 / 68 A6, 6 PR
TL/TT	TL
Hub design	Fork assembly
Type of bearing	Ball bearing
Shaft diameter [mm].	25
Mounting length [mm]	90
Hub length [mm]	90
Rim colour	Silver
Load capacity complete wheel [kg]	355
Speed complete wheel [km/h]	15



Technical Informations

Assembly Item no. Tyres	• 15710380
LI / SI / PR	72 A3 / 68 A6, 6 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 315
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

Maximum air pressure [bar].	2,90
Section width (mm)	155
Stat. radius (SLR) [mm]	182
Rolling circumference [mm].	1183
Tread depth (mm)	10,0
Assembly Item no. Rim	• 30895220
Valid rim size	5.50 A x 8
Load capacity of rim 1 [kg]	530
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	500
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	30
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Number of drain holes	3
Verschweißung beidseitig	No
Offset hub	No
Additional socket required	No
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0