

WHEELS

Product group	Wheels
Item number	59996072
Valid wheel size	155 / 70 R 13
Brand	Boka Trailer Line
Tread pattern	FT 01
Valid rim size	4 J x 13 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	437
Speed complete wheel [km/h]	140



BOKA TRAILER

Technical Informations

Assembly Item no. Tyres	• 18545330
LI / SI / PR	79 N
Load capacity 1 [kg]	437
Speed 1 [km/h].	140
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	11,10
ECE regulation number	ECE 30 ECE 117
Section width (mm)	153
Tread depth (mm)	6,1

Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 39600659
Load capacity of rim 1 [kg]	525
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Maximum air pressure [bar].	3,00
Type of drive	Towed axle
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	4
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100
Valve seat	External Valve
Valve hole diameter [mm]	11.3

Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade