

TYRES

| | |
|-----------------------|--------------------|
| Product group | Tyres |
| Item number | 71800225 |
| Valid tyre size | 18.00 R 25 |
| LI / SI / PR | 207 A5 / 214 A5 |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Portmax PM 90 |
| Sonderpostenkategorie | Damaged |
| type of damage | Crack in the tread |



Notes and features

- The BKT Portmax PM 90 was specially developed for container handling equipment like reach stackers.
- Its optimum contact area enables even weight distribution.
- Thanks to its strong casing and reinforced sidewalls, the tyre provides excellent stability in lift mode.
- The deep tread pattern with the wide, centre rib and the wear-resistant tread compound ensure the tyre's long service life.
- Its optimal lug angle with reinforced shoulders minimises tyre damage.
- The tyre is able to dissipate static charge from the vehicle.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 71800225 |
| Valid tyre size | 18.00 R 25 |
| LI / SI / PR | 207 A5 / 214 A5 |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Portmax PM 90 |
| Antistatic | Yes |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 0,00 |
| Recommended rim size | 13.00 |
| Section width (mm) | 495 |
| Outer diameter of tyre [mm]. | 1655 |
| Stat. radius (SLR) [mm] | 730 |
| Rolling circumference [mm]. | 5024 |
| Tread depth (mm) | 63,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 207 A5 | 17500 | 25 | | | |
| 214 A5 | 21200 | 25 | | | |