

## **TYRES**

Product group	Tyres	
Item number	72000660	
Valid tyre size	23.1 - 26	
LI / SI / PR	172 A2 / 160 A6, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 345	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted	





## Notes and features

- The Alliance Forestar 345 was developed for use on heavy forestry machines and logging equipment operating in challenging conditions.
- The tyre provides high traction and low slip, even without chains.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls, the tyre is very tough and durable.
- Thanks to its high lugs and especially hard-wearing rubber compound, the tyre is optimally suited to demanding forest applications.
- It is the ideal tyre for skidders.



## **Technical Informations**

Item number	72000660
Valid tyre size	23.1 - 26
LI / SI / PR	172 A2 / 160 A6, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 345
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	0,00
Recommended rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	587
Outer diameter of tyre [mm].	1610
Stat. radius (SLR) [mm]	734
Rolling circumference [mm].	4781
Tread depth (mm)	47,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		2,40	
160 A6	4500	30		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.