

TYRES

Product group	Tyres
Item number	72200057
Valid tyre size	250 / 75 R 16
LI / SI / PR	120 G
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
Sonderpostenkategorie	Damaged
type of damage	Flap damage



Notes and features

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in on-road and off-road applications.
- The tread pattern ensures rapid self-cleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.



Technical Informations

Item number	72200057
EAN	4040658145643
Valid tyre size	250 / 75 R 16
LI / SI / PR	120 G
TL/TT	TL
Brand	Nokian
Tread pattern	TRI 2
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	21,00
Maximum air pressure [bar].	4,50
Section width (mm)	258
Outer diameter of tyre [mm].	782
Stat. radius (SLR) [mm]	363
Rolling circumference [mm].	2390
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 G	1400	90		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.