

TYRES

Product group	Tyres	
Item number	72200076	
Valid tyre size	15 x 6.00 - 6	
LI / SI / PR	59 A6 / 70 A6, 6 PR	
TL/TT	TL	
Brand	Deli	
Tread pattern	S-247	
Sonderpostenkategorie	DOT	
type of damage	DOT	



Notes and features

• Agricultural tyre with traction tread pattern.



Technical Informations

Item number	72200076
Valid tyre size	15 x 6.00 - 6
LI / SI / PR	59 A6 / 70 A6, 6 PR
TL/TT	TL
Brand	Deli
Tread pattern	S-247
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	3,18
Recommended rim size	4.50
Maximum air pressure [bar].	3,10
Section width (mm)	155
Outer diameter of tyre [mm].	372
Stat. radius (SLR) [mm]	166
Rolling circumference [mm].	1086
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
59 A6	243	30	Drive Wheel	3,10	
70 A6	335	30	Free Rolling	3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.