

TYRES

Product group	Tyres
Item number	72200229
Valid tyre size	IF 520 / 85 R 42
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372
Sonderpostenkategorie	Disassambled
type of damage	Puncture at tyre shoulder



Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



Technical Informations

Item number	72200229
Valid tyre size	IF 520 / 85 R 42
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	223,50
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	540
Outer diameter of tyre [mm].	1955
Stat. radius (SLR) [mm]	879
Rolling circumference [mm].	5825
Tread depth (mm)	55,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	569
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.