

TYRES

Product group	Tyres
Item number	72200257
Valid tyre size	320 / 55 - 15
LI / SI / PR	112 B, 10 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Multi Trac C/S
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



Notes and features

- Tyre for professional use on lawns, gardens and golf courses.
- Durable rubber compound in conjunction with deep tread blocks.
- Tread pattern optimised for stability and traction.

Technical Informations

Item number	72200257
Valid tyre size	320 / 55 - 15
Alternative size 1	29x12.50-15
LI / SI / PR	112 B, 10 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Multi Trac C/S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	18,00
Recommended rim size	10.00
Permitted rim size	10LB
Maximum air pressure [bar].	4,14
Section width (mm)	318
Outer diameter of tyre [mm].	737
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2291
Tread depth (mm)	8,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 B	1120	50		4,10	
	1344	25		4,14	